

fuge



Bench-top & refrigerated centrifuges

Versatile bench-top centrifuges featuring optional refrigeration and multiple rotor configurations.

EU
COMPLIANT
REFRIGERANT





Bench-top and refrigerated centrifuges

EZEEfuge centrifuges are a simple and cost effective solution to bench-top centrifugation requirements.



DISPLAY

A large multi-colour Touchscreen display provides clear indication of running conditions including rotor, speed, RCF and time. The touchscreen gives you ease of control and a modern feel. An advanced microprocessor controller allows setting/displaying of the rotational speed in either RPM or RCF. The screen is splash-proof and protects the inner electronics from external elements.



PERFORMANCE

Customisable programmes allow you to choose between 15 acceleration and deceleration profiles to suit your protocols (zero brake option available), ensuring your samples get the best separation. The frequency variable motor drive system enables the unit to operate in a stable and quiet manner. A pre-cool function allows the set temperature to be reached rapidly before samples are added.


FLEXIBILITY

EZEEfuge simplifies sample processing with up to 20,625 x g, and a tube capacity up to 12 x 5 ml. The rotor portfolio supports labware including PCR tubes, strip tubes, 2ml microtubes, to 5ml tubes.

CONVENIENCE

EZEEfuge enables users to edit and store up to 40 programs with a combination of speed, centrifugal force, running time, acceleration/ deceleration rate, saving time on protocol set-up without having to re-enter parameters.

AVAILABLE ROTORS



EZEERotor-0.2
8 x 0.2ML PCR STRIPS



EZEERotor-5
12 x 5ML TUBES



EZEERotor-2*
24 x 1.5/2ML TUBES

*Standard EZEEfuge package includes EZEERotor-2

CATALOGUE NO.	EZEEFUGE	EZEEFUGE-R-EU
MAX RPM	16,500	16,500
RPM ACCURACY	±10RPM	±10RPM
MAX RCF xg	20,625	20,625
CAPACITY	8 x 0.2ML PCR STRIPS 24 x 1.5ML/2ML TUBES 12 x 5ML	8 x 0.2ML PCR STRIPS 24 x 1.5ML/2ML TUBES 12 x 5ML
TIMER	1s - 99H 59 MIN 59s	1s - 99H 59 MIN 59s
TEMP RANGE		-20°C ~ 40°C
TEMP ACCURACY		±1.0°C
UNIT DIMENSIONS (WxDxH)	270 x 335 x 245 MM	295 x 470 x 330 MM
WEIGHT	15 Kg	35 Kg



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.