



Power Supplies



	MINI		MIDI	MAXI	MAXI
	nanoPAC-300P	nanoPAC-500	powerPRO-300	powerPRO-500	powerPRO-3AMP
Output range					
Volts	10-300V	10-500V	5-300V	5-500V	5-300V
Current	10-400mA	10-400mA	1-700mA	1-800mA	10-3000mA
Power	60W max.	120W max.	150W	300W	300W
Resolution	1V / 1mA	1V / 1mA	1V / 1mA / 1mW	1V / 1mA / 1W	1V / 1mA / 1W
Type of output	constant voltage or constant current		constant voltage, constant current or constant power, programmable		
Automatic crossover	–	–	✓	✓	✓
Timer	1-999 min. with alarm; intensity continuous		constant mode: 1-999 min. with alarm; continuous. programmable mode: 1-999 min. with alarm; continuous.		
Pause/resume function	✓	✓	✓	✓	✓
Display	3-digit LED	3-digit LED	2.4" LCD display	2.4" LCD display	2.4" LCD display
Programmable Methods	2 step-program	2 step-program	Up to 30 programmable files, each with 6 steps. Preset options for Cleaver gel tanks.		
Safety features	no load detection; shrouded plugs and sockets; over temperature protection; over load detection		no load detect; leakage detect; over temperature protection; over load detection; sudden load change detection (could be disabled by proper setting); shrouded plugs and sockets		
Operating conditions	ambient-40°C; ±95% humidity	ambient-40°C ; ±95% humidity	ambient-40°C; ±95% humidity	ambient-40°C ; ±95% humidity	ambient-40°C ; ±95% humidity
Stackable	X	X	✓	✓	✓
Number of output jacks	2 sets in parallel	2 sets in parallel	5 sets in parallel	5 sets in parallel	5 sets in parallel
Regulatory conformity	ETL, CE, FCC	ETL, CE, FCC	ETL, CE, FCC	ETL, CE, FCC	ETL, CE, FCC
Rated voltage	100-240 VAC	100-240 VAC	100-240 VAC	100-240 VAC	100-240 VAC
Construction	polycarbonate housing with aluminium base		flame retardant ABS-plate design		
Dimensions (WxDxH)	140 x 191 x 84mm	140 x 191 x 84mm	215 x 335 x 104mm	215 x 335 x 104mm	215 x 335 x 104mm
Weight	1kg	1kg	2.1kg	2.1kg	2.1kg



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.