

ShallowBaths™ Series Unstirred Water Baths



Clifton ShallowBaths™ are available in digital or analogue option. Perfect for heating small height samples such as micro tubes, micro plates and bottles. These shallow baths require less water and less process chemicals, so are therefore economical to use.

Comprising of a high quality corrosion resistant stainless steel tank, with a bright clean finish housed in a durable painted outer case. Painted surfaces feature anti-bacterial finish with good chemical resistance.

NE2 - 2D		NE2 - 5D	NE2 - 9D	NE1 - 9
GENERAL				
Temp. Range	Ambient + 5°C - 99°C			
Temp. Alarm	Over temperature alarm is automatically set 4°C above set point			
Temp. Control	PID Digital, LED display showing actual or set temperature, resolution 0.1°C			Graduated in 5°C increments
Sensitivity/Uniformity	±0.2°C / ±0.1°C			±0.25°C / ±0.25°C
Heater Power (220-240V)	200W	800W		
Voltage	120V or 230V models available 50-60Hz			
DIMENSIONS				
Tank Capacity	2 Litre	5 Litre	9 Litre	
External (mm)	332w x 185d x 135h	361w x 332d x 135h	535w x 332d x 135h	
Internal (mm)	300w x 150d x 65h	325w x 300d x 65h	500w x 300d x 65h	
Water Level Max. (mm)	40			
Water Level Min. (mm)	20			

[Accessories on Page 14-17](#)



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.