



OAKTON®

WATERPROOF PHTESTRS®

SETTING THE STANDARD FOR
POCKET PH TESTERS!



 **Cole-Parmer®**
Delivering Solutions You Trust

Oakton® Waterproof pHTestrs®

MAKE OAKTON WATERPROOF PHTESTRS YOUR FIRST CHOICE FOR QUALITY!

For over 18 years, Oakton Instruments has set the standard for innovation and quality in electrochemical instrumentation. From their introduction in 1991 of the world's first microprocessor-based, pocket-sized pH meter, to their new EcoTestr™, Oakton has met or exceeded user expectations. Today, Oakton remains in the forefront with technical innovations that permit intuitive, user-friendly operation and allow handheld instruments to easily fit in your hand.

All Oakton meters are designed and manufactured at an ISO 9001 facility, and meet CE requirements for EMF. Their commitment to delivering accuracy, quality, and reliability at a competitive price makes Oakton a perennial leader in their field.



EASY-TO-REPLACE SENSOR MODULES*



- Twist off the module, replace, then twist back on; that's all it takes—no tools are ever required!
- Self-diagnostic error messages help you determine when it's time to change the sensor
- Economical way to get the equivalent of a new meter at nearly half the cost

UNIQUE OAKTON DOUBLE-JUNCTION REFERENCE SYSTEM* PROTECTS THE ELECTRODE FROM CHEMICAL ATTACK

- Kynar® PVDF double-junction reference is a standard feature on the big-digit pHTestr series. Compare this to the single-junction reference included on other brands
- Dependable and long-lasting! Design prevents precipitation at the reference junction that can lead to inaccurate readings or shortened service life
- Use with confidence—even with demanding samples containing sulfides, heavy metals, organics, Tris buffer, or protein
- Great for wastewater, chemical applications, life science labs, food testing of wine or milk—anywhere ordinary testers with single-junction electrodes are impractical!

*Features are not found on EcoTestr or models with BNC electrode connection.

PHTESTRS® ARE BUILT TO STAND UP TO REAL USE!

- Valox® plastic body is resistant to most chemicals used in laboratories and industrial sites. Compare this to the ordinary plastics used by the other manufacturers
- If you drop your pHTestr in the lake or in the mud, the unit's IP67-rated, 100% dustproof and waterproof housing ensures your instrument will remain unaffected. Testrs will even float for easier recovery
- pH sensor features a recessed design to protect the glass bulb against impact because you have more important things to worry about than pampering a pocket pH tester
- All models feature either automatic or manual temperature compensation to ensure accuracy in the midst of fluctuating temperatures
- Lanyard connection allows you to hang your pHTestr from your neck so you always know where it is. Quick-release lanyard is included. EcoTestr™ features a belt/pocket clip to keep it accessible when not in use.
- All pHTestrs can be stored dry without affecting the sensor's life span or accuracy. No need to carry around storage solution



OAKTON® WATERPROOF pHTESTR® 10 BNC

Temperature Compensation

Temperature compensation is fixed at 25°C for most common uses. Manual temperature compensation is also available for reading at user-selectable temperature points.

Compatible with any pH Electrode using a BNC Connector

Tailor your pHTestr to suit your application. Epoxy, glass, direct-connect, or cabled electrodes can all be used. Great option for accessing tight places!



OAKTON WATERPROOF ORPTESTR® 10 AND ORPTESTR 10 BNC

Convenient Way to Determine Oxidation-Reduction Potential

Ideal for ORP applications in the ± 999 -mV range—including industrial waste treatment, oxidation of cyanide, pulp bleaching, bleach manufacturing, and water sanitation.

CHOOSE FROM TWO ORPTESTRS

ORPTestr 10 features an easy-to-replace double-junction, platinum band sensor. Use without worry in harsh, dirty samples.

ORPTestr 10 BNC allows you to use any ORP electrode with a BNC connector. Create a custom meter based on your specific requirements.



OAKTON® WATERPROOF PH SPEAR

Open-Pore Reference Junction

The pH Spear electrode junction is 200 times larger than standard electrodes. This virtually clog-free design combined with the spear-tipped shape is perfect for pH determination in solid and semisolid samples such as cheese, meats, fruits, bread, and soil, etc.



User-Replaceable, Double-Junction Sensor

Chemical-resistant Kynar® PVDF double-junction sensor minimizes contamination and extends sensor life. Replacement sensors save over the cost of a new pH Spear.



Rugged Spear Tip

Electrode is polymer-enclosed—designed tough to pierce samples and provide stable measurements. Low-maintenance unit requires only periodic cleaning with a mild detergent and water.



Easy-to-Read Display

Large LCD features over-sized digits for at-a-glance visibility. Ergonomic design allows you to read as you measure—no need to tilt your head or remove the tester from your sample.

Temperature Compensation

Temperature compensation is fixed at 25°C for most common uses. Manual temperature compensation is also available for reading at user-selectable temperature points.



Spear Tip Can Also Fit into Small Vessels

Great for laboratory applications that use test tubes and microtubes. Less costly than standard micro pH electrodes.

PERFORMANCE SPECIFICATIONS



Operating temperature:

32 to 122°F (0 to 50°C)

Power:

four 1.5 V batteries (included)

Battery life:

200 to 500 hours

Catalog number	ML-35423-10	ML-35634-10	ML-35634-14	ML-35634-20	ML-35634-30	ML-35650-10	ML-35650-14	ML-35634-40
Model	EcoTestr pH 2	pHTestr 10	pHTestr 10 BNC	pHTestr 20	pHTestr 30 w/temp display	ORPTestr 10	ORPTestr 10 BNC	pH Spear
Range	0.0 to 14.0 pH	-1.0 to 15.0 pH	-1.00 to 15.00 pH			-999 mV to +1000 mV		-1.00 to 15.00 pH
Resolution	0.1 pH	0.1 pH	0.01 pH			1 mV		0.01 pH
Accuracy	±0.1 pH	±0.1 pH	±0.01 pH			±2 mV		±0.01 pH
Temperature compensation	Automatic	Automatic	Fixed at 25°C or manual	Automatic		None		Fixed at 25°C or manual
Dimensions	6¼"L x 1⅝"W x 1⅞"H	6½"L x 1½" dia			6½"L x 1½" dia		8½"L x 1½" dia	
Replacement sensor	N/A	ML-35624-38	N/A	ML-35624-38		ML-35650-09	N/A	ML-35634-50

What's included:

- All Testrs include 1.5 V button cell batteries
- All Oakton® pH Testrs (except EcoTestr pH 2 and pH Spear) are shipped in a protective plastic case



Easy twist-off battery compartment



Protective plastic case

pHTestr® Calibration Kits

Include pHTestr, calibration pouches (two each of pH 4.01, 7.00, 10.00, and rinse water), sample jar, and sturdy carrying case.

[ML-35634-70](#) pHTestr 10 calibration kit

[ML-35634-80](#) pHTestr 20 calibration kit

[ML-35634-90](#) pHTestr 30 calibration kit





WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.