

## Product Name CMS500



### Key Features

- +2°C to +8°C temperature range
- Core temperature display, represents your vaccine vial through iCOOL temperature probe
- External digital controller and temperature display
- Battery Back up
- Annual service & Calibration available
- Fitted lock with 2 keys



#### Controller

Controller system. Read, Record, Reset with the touch of one button. Adjustable temperature setting.



#### Battery

Backup Should there ever be a power outage the battery backup will continue to monitor the internal temperature of the fridge.



#### Porthole

Factory fitted porthole enables quick and easy access for any secondary temperature monitoring probes.



#### Flexible Storage

Multiple shelf locations. Back stop on every shelf provides a flexible storage solution.



#### LED Lighting

Low voltage LED lighting, improves running cost as no heat is produced. Long lasting

Product Name CMS500

| Details                      |                          |
|------------------------------|--------------------------|
| Gross Capacity (litres)      | 495                      |
| Net Capacity (litres)        | 480                      |
| Unit External Width (mm)     | 1180                     |
| Unit External Depth (mm)     | 609                      |
| Unit External Height (mm)    | 1530                     |
| Product Weight (kg)          | 120                      |
| Packed Width (mm)            | 1230                     |
| Packed Depth (mm)            | 655                      |
| Packed Height (mm)           | 1710                     |
| Packed Weight (Kg)           | 132                      |
| Temperature Range            | +2°C to +8°C             |
| External Finish              | Painted Steel            |
| Internal Finish              | Painted Steel            |
| Battery Back up              | No                       |
| Door Finish                  | Painted Steel            |
| Door Type                    | Solid                    |
| Door Style                   | 2 doors Hinged           |
| Door Open Depth (mm)         | 1140                     |
| Replacement Door Seal        | No                       |
| Open Door Sensor             | Yes                      |
| Lock                         | 2 Locks, 4 Keys          |
| Adjustable Feet (number)     | 4 Lockable Castors       |
| Porthole                     | Yes                      |
| Porthole location            | Rear, Middle             |
| Temperature Display on Panel | Yes                      |
| Temperature Alarm            | Yes                      |
| Remote Alarm Contacts        | Yes                      |
| Audible Alarms               | Yes                      |
| Visual Alarms                | Yes                      |
| Number of Shelves            | 8 (6 full size & 2 Base) |
| Number of Shelf Positions    | 10+                      |
| Shelf Material               | Plastic Coated Wire      |
| Interior Light               | Yes                      |
| Light Type                   | LED                      |
| Light Activation             | Switch                   |
| Fan                          | Yes                      |
| Spark Free                   | No                       |
| Controller Type              | Digital, External        |
| Number of Probes             | 2                        |
| Probe Type                   | Air                      |
| Ambient Temperature Range    | +10c to +30c             |
| Refrigerant Type             | R600a                    |
| CFC Free                     | Yes                      |
| HCFC Free                    | Yes                      |
| Ammonia Free                 | Yes                      |
| UK 3 Pin Plug                | Yes                      |
| Voltage Supply               | 220-240V / 50Hz          |
| Wall Brackets                | No                       |
| Optional Digital Lock        | No                       |
| Certification                | CE/UK                    |
| Noise Level (dbA)            | 50                       |
| Input Power (W)              | 380                      |
| Cable Length (CM)            | 20                       |
| Energy Consumption (KW/ 24h) | 2.7                      |



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.