

Distilling

Evaporation Solutions!
Leading Laboratory & Industrial Rotary evaporator

Rotary evaporator is an indispensable equipment for processes of evaporation, concentration, crystallization, drying, separation, and solvent recovery in many fields, and it is mainly used for continuous distillation of large amounts of volatile solvents under reduced pressure. It can be applied in different areas such as biological, pharmaceutical, chemical and even food & beverage industries.

DLAB Rotary Evaporator models:

Series	Image	Evaporating Flask Volume	Evaporation capacity	Temperature range	Automatic lifting	Display	Page
RE100-Pro		50-3000mL	Max.1.56L/h (H ₂ O)	RT-180°C	YES	LCD	p.90
RE100-S		50-3000mL	Max.1.56L/h (H ₂ O)	RT-180°C	No (Manual lifting)	LCD	p.91
RE200-Pro		20L	Max.4.5L/ h(75% Alcohol)	RT-180°C	YES	LCD	p.88
RE500-E		5L	Max.2L/h (75% Alcohol)	20-100°C	YES	LCD	p.95
RE1000-E		10L	Max.3.8L/h (75% Alcohol)	20-100°C	YES	LCD	p.95
RE2000-E		20L	Max.5L/h (75% Alcohol)	20-100°C	YES	LCD	p.95
RE5000-E		50L	Max.11L/h (75% Alcohol)	20-100°C	YES	LCD	p.95

RE200-Pro

20L Industrial Digital Rotary Evaporator

A promise of safety, reliability & highest level of efficiency for large volumes



Features

- Large LCD digital display with heating temperature, rotation speed, clockwise&anticlockwise and time information
- One-click automatic motor lifting (stroke 180mm), smooth and silent
- Water/ oil heating bath with wide temperature range from RT to 180 °C
- Speed range from 10 to 150rpm, and interval operation in clockwise and anticlockwise directions for drying process
- Two-section vertical triple coil condensing tube with large area and strong evaporation capacity ensuring high-efficiency sample recovery
- The connector device allows for easy and quick installation of the evaporating flask
- PTFE double sealing ring with excellent sealing performance
- Switch valve for continuous collection without compromising the system vacuum and solvent distillation

Applications

Suitable for pilot-scale production, large-scale application in biology engineering, pharmaceutical industry, chemical industry, beauty industry, medical industry and food processing.



Large LCD display



Overheating protection



Chemical resistance



Two-section vertical triple coil condenser

large condensation area and strong evaporation capacity ensuring high efficient sample recovery



Switching valve design

switch valve for continuous collection without compromising the system vacuum and solvent distillation



Heating bath

- Water & oil bath
- Enhanced lifetime through exclusive use of corrosion-free stainless-steel
- It adopts special heat insulation structure design so the surface temperature is far lower than the temperature in the bath to avoid personnel burns

Specifications	RE200-Pro	
performance	Temperature range	Room temp. ~180°C (water and oil bath)
	Temperature control accuracy	Water: $\pm 1^{\circ}\text{C}$ Oil: $\pm 3^{\circ}\text{C}$
	Rotation Speed	10~150rpm
	Ultimate vacuum	Less 2.6mbar
	Evaporation capacity	Max.4.5L/h(75% Alcohol)
function	Temperature control	Micro processor PID control
	Display	LCD (temperature/speed/clockwise and Anti-clockwise/time)
	Time Setting Range	0-999min
	Lift stroke	Motorized 180mm
	Safety features	Motor over-current protection, earth-leakage protection, lifting overload protection, Boil-dry protection, Overheating protection
components	Evaporation flask	Round flask 20L
	Receiving flask	Round flask 10L with drain valve
	Condenser	Two-section vertical triple coil condenser, cooling surface 1.2m ²
specification	Heating bath size	Ø 450×240mm
	Hose connection	Cooling/suction nozzle outer diameter 16mm, vacuum pump nozzle outer diameter 16mm
Dimension[D×W×H]		1160×600×1860mm
Voltage/Frequency		220V/50/60Hz
Power		4600w
Heating Power		4400w

RE100-Pro

Digital Rotary Evaporator

It is highly used in chemical industries, pharmaceutical industries and also higher learning institution

Features

- Digital LCD display of both rotation speed and heating temperature allows for optimal control of all distillation processes
- Automatic motor lift releases the evaporating flask to a safe position in case of power failure
- 5L heating bath with wide temperature range from room temperature to 180 °C Water/oil heating mode can be changed only through a switch
- Overheating protection temperature at 220 °C
- Boil-dry protection, automatically power off if heating without water/oil in the heating bath
- Speed range from 20 to 280rpm, and interval operation in clockwise and anticlockwise directions for drying process
- Condenser (cooling surface 1700cm²) with excellent cooling effect
- Ejection mechanism ensures easy removal of evaporating flask
- Double spring sealing ring made of PTFE provides an excellent sealing performance
- Optional glassware with explosion proof film available



Large LCD display



USB connector



Chemical resistance



Overheating protection



Compatible with all range of glassware

Specifications	RE100-Pro
Evaporating Flask Volume	50-3000mL(Optional Thickened glass axis compatible with 3L evaporating flask)
Motor Type	Brushless DC motor
Speed Range	20-280rpm
Display	LCD(speed, temperature, time)
Direction of Rotation	Clockwise and counterclockwise
Heating Temperature Range	Room temp. to 180°C
Control Accuracy	water: $\pm 1^{\circ}\text{C}$ oil: $\pm 3^{\circ}\text{C}$
Evaporation capacity	Max.1.56L/h(H ₂ O)
Heating Power	1300W
Lift stroke	Motorized 150mm
Timer	Yes
Time Setting Range	1-999min
Dimension[D×W×H]	465×457×583mm
Weight	15kg
Permissible Ambient Temperature	5-40°C
Permissible Relative Humidity	80%RH
Protection Class	IP20
USB Interface	Yes
Voltage/Frequency	100-120/200-240V, 50/60Hz
Power	1400W

RE100-S

LED Digital Rotary Evaporator

DLAB LED Digital Rotary Evaporator is a basic chemical laboratory instrument suitable for evaporation, distillation and separation of chemicals. It can be used as a multifunctional system in combination with vacuum pump, vacuum controller and low temperature circulators to provide excellent distillation solutions in many laboratory applications.

Features

- 5L heating bath with a wide temperature range (room temp. to 180°C). Independent temperature control makes it can be used separately. Water/oil heating mode can be changed just through a switch
- Manual lift combined with auxiliary lift for precise positioning of the glassware
- PID control ensures high temperature accuracy at $\pm 1^\circ\text{C}$ (water)
- Overheating protection temperature at 220°C
- Boil-dry protection, automatically power off if heating without water/oil in the heating bath
- Speed range from 20 to 200rpm, timing interval operation in clockwise and anticlockwise directions for drying process
- Condenser (cooling surface 1200/1700cm² for selection), speeding up the flow rate of liquid with excellent cooling effect
- Ejection mechanism ensures easy exchange of evaporating flask
- Adjustable immersion angle
- Double spring sealing ring which is made of PTFE provides an excellent sealing performance
- Compatible with the entire range of RE100-Pro glassware
- Optional glassware with explosion proof film available
- High temperature warning when above 50°C



Chemical resistance



Overheating protection



Compatible with wide range of glassware



Specifications	RE100-S
Evaporating Flask Volume	50-3000mL (Optional Thickened glass axis compatible with 3L evaporating flask)
Motor Type	Brushless DC motor
Speed Range	20-200rpm
Display	LED(speed, temperature, time)
Direction of Rotation	Clockwise and counterclockwise
Heating Temperature Range	Room temp. to 180°C
Control Accuracy	water: $\pm 1^\circ\text{C}$ oil: $\pm 3^\circ\text{C}$
Evaporation capacity	Max. 1.56L/h(H ₂ O)
Heating Power	1200W
Lift stroke	Manual 110mm+auxiliary 100mm
Interval Time Setting Range	1-999s
Dimension[D×W×H]	Main Unit: 440×320×450mm Heating Bath: 300×300×240mm
Weight	Main Unit: 7kg Heating Bath: 3kg
Permissible Ambient Temperature	5-40°C
Permissible Relative Humidity	80%RH
Protection Class	IP20
USB Interface	Yes
Voltage/Frequency	100-120/200-240V, 50/60Hz
Power	1245W

Vertical

Cat. No.	Glassware type	Volume	Cooling surface
18900165	Evaporating flask(NS29/32) Receiving flask(KS35/20)	1000mL	1700cm ²
18900173	Evaporating flask(NS24/40) Receiving flask(KS35/20)	1000mL	1700cm ²
18900166	(COATED)Evaporating flask(NS29/32) Receiving flask (KS35/20)	1000mL	1700cm ²
18900174	(COATED)Evaporating flask(NS24/40) Receiving flask (KS35/20)	1000mL	1700cm ²
18202410	Evaporating flask (NS 29/32) Receiving flask (KS 35/20)	1000mL	1200cm ²
18900476	Evaporating flask (NS 24/40) Receiving flask (KS 35/20)	1000mL	1200cm ²

Diagonal

Cat. No.	Glassware type	Volume	Cooling surface
18900163	Evaporating flask(NS29/32)Receiving flask(KS35/20)	1000mL	1700cm ²
18900171	Evaporating flask(NS24/40)Receiving flask(KS35/20)	1000mL	1700cm ²
18900164	(COATED)Evaporating flask(NS29/32) Receiving flask (KS 35/20)	1000mL	1700cm ²
18900172	(COATED)Evaporating flask(NS24/40) Receiving flask (KS35/20)	1000mL	1700cm ²

Heating Bath

Cat. No.	Description	Volume
18900201	Heating bath for Rotary Evaporator RE100-Pro, 220V	5L
18900202	Heating bath for Rotary Evaporator RE100-Pro, 110V	5L
6033100210	LED heating bath, 100V-120/200-240V,50/60HZ	5L

Heating Bath Lid

Cat. No.	Description
18900547	heating Bath lid for RE100-S, improve distillation efficiency & ensure personnal safety from liquid splash

Glassware



Evaporating flask

Cat. No.	Volume	Size
18300116	50mL	NS 29/32
18300117	100mL	NS 29/32
18300118	250mL	NS 29/32
18300119	500mL	NS 29/32
18300120	1000mL	NS 29/32
18300121	2000mL	NS 29/32
18300122	3000mL	NS29/32
18300655	50mL	NS24/40
18300201	100mL	NS 24/40
18300202	250mL	NS 24/40
18300203	500mL	NS 24/40
18300204	1000mL	NS 24/40
18300205	2000mL	NS 24/40
18900204	3000mL	NS24/40
18900563	20L	RE200-Pro



Foam brake

Cat. No.	Volume	Size
18300093	250mL	NS 29/32
18300207	250mL	NS 24/40



Glass axis

Cat. No.	Volume	Size
18100998	Glass axis	NS 29/32
18203431	Thickened glass axis	NS24/40
18300206	Glass axis	NS 24/40
18204253	Thickened glass axis	NS29/32



Receiving flask

Cat. No.	Volume	Size
18300107	100mL	KS 35/20
18300108	250mL	KS 35/20
18300109	500mL	KS 35/20
18300110	1000mL	KS 35/20
18300111	2000mL	KS 35/20
18900564	10L	RE200-Pro



Distilling spider with 5 flasks(without flask)

Cat. No.	Volume	Size
18900194	/	NS 29/32, NS24/29
18900177	/	NS 29/42, NS24/40



Connector

Cat. No.	Volume	Size
18300094	/	NS 29/32, NS24/29
18300095	/	NS 29/32, NS19/26
18300096	/	NS 29/32, NS14/23
18300199	/	NS24/40, NS19/22
18300200	/	NS 24/40, NS14/20
18900193	/	NS 24/40, NS 29/42

Optional Add-ons

Distillation System Connection (For RE100-Pro&RE100-S)



C410 Chemistry-design diaphragm pump

Specifications

Maximum Vacuum:13mbar
Work Mode: Continuous Operation
Nozzle Size:8mm, Power: 95W
Motor speed:1450rpm
Flow Rate:

mbar	1000	880	750	600	480	280
L/min	25	22	20	12	7.5	50

Noise:50dB

Seals and other accessories

Cat. No.	Description	
18204186	vacuum seal (PTFE+Viton)	
18204187	Evaporation bottle spring Used with 18204186	
18900190	Evaporation flask clip(red) NS29/42	
18900188	Evaporation flask clip(green) NS24/40	
18900744	Rotary Evaporator transparent safety shield(RE100-Pro)	
18900789	Rotary Evaporator transparent safety shield(RE100-S)	
18204228	Flask holder(50mL-1000mL)	
	Flask holder(1L-20L)	

Regulator /Moisture

Cat. No.	Description	
18900186	Material: PVDF, PTFE, ABS, Borosilicate Glass, Stainless Steel	

RE500-E&RE1000-E& RE2000-E&RE5000-E

Pilot Scale Digital Control Rotary Evaporator

Features

- LCD digital display with intuitive interface for operation and control.
- PID controller, precise control, fast setting.
- Stepless automatic motor lifting of the heat bath, smooth and silent.
- The reciprocation rotation function is the most useful for concentration of sample with power or solid particles.
- Double-layer high-efficiency condenser with anti-backflow design, large condensation surface area, strong evaporation capacity is a guarantee of high efficient sample recovery.
- Professional air tightness system design with PTFE sealing ring, featured with heat/corrosion resistance, and high durability.
- Optional vacuum controller to control the vacuum degree freely.
- Keep the outer surface of the heat bath at mild temperature with proprietary heat insulation design to avoid accidental personnel burn injury.
- Equipped with automatic switching valve, continuous collection can be carried out without affecting the negative pressure index of the system and solvent distillation.
- Optional water bath/oil bath heating mode (standard water bath).
- Solution can be continuously fed into evaporating flask.
- Digital display steam temperature sensing device can feed back the solvent steam temperature in real time



Specification

Photos				
Model	RE500-E	RE1000-E	RE2000-E	RE5000-E
Evaporating flask volume	5L	10L	20L	50L
Speed range	20-180	20-130	20-130	20-130
Display	LCD			
Evaporation Capacity (Max.L/h) For 75% Alcohol	2	3.8	5	11
Ultimate vacuum	9 mbar			
Timer	Yes			
Temperature range	20-100°C			
Temperature control accuracy [°C]	±1			
Heating Power [W]	2000	3000	4000	5000
Temperature Display	LCD			
Lifting mode	Motorized			
Lifting Stroke [mm]	130	200	180	253
Time Setting Range	0-999min			
Voltage	220V			
Frequency [Hz]	50/60			
Motor	Brushless DC motor			
Heat Bath	Teflon coating			
Protection Class	IP20			
Dimension[D×W×H]	600*290*720	790*480*1130	900*490*1320	1030*510*1370
Permissible ambient temperature [°C]	5-40			
Permissible ambient humidity	≤80%			
Safety features	Motor over current protection, earth leakage protection, dry heating protection, overheat protection function			

Vertical

Cat. No.	Glassware type & Volume	Cooling surface
18900674	5L Main condenser	0.28m ²
18900639	10L Main condenser	0.49m ²
18900640	10L Secondary condenser	
18900688	20L Main condenser	1.29m ²
18900689	20L Secondary condenser	
18900648	50L Main condenser	1.75m ²
18900649	50L Secondary condenser	

**Evaporating flask**

Cat. No.	Volume	Size
18900677	5L	RE500-E
18900643	10L	RE1000-E
18900690	20L	RE2000-E
18900650	50L	RE5000-E

**Receiving flask**

Cat. No.	Volume	Size
18900678	3L	RE500-E
18900644	5L	RE1000-E
18900691	10L	RE2000-E
18900651	20L	RE5000-E

**Three way bottle**

Cat. No.	Volume	Size
18900676	—	RE500-E
18900642	—	RE1000-E/RE2000-E/RE5000-E

**Rotation axis**

Cat. No.	Volume	Size
18204087	—	RE500-E
18204034	—	RE1000-E/RE2000-E/RE5000-E



Other accessories

Cat. No.	Description	Size	Photograph
18900683	5L Locking clamp	30#	
18900682		40#	
18900655		50#	
18900656		60#	
18900657		80#	
18204035	5L Vacuum sealing ring	Teflon + fluorine rubber	
18203979	10L/20L/50L Vacuum sealing ring		
18204228	Flask holder (50mL-1L and 1L-20L)	90mm	
		160mm	



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.