

EcoVac

Economical Vacuum Aspirator

Small, compact and easy to use system for the convenient handling of liquid waste disposal.

Easy to switch between manual aspiration and two-level adjustable continuous aspiration:
Level 1: Standard continuous aspiration mode.
Level 2: Fast continuous aspiration mode enhanced

Hanging handles on both sides

Vacuum level indicator light



Features

- Small and compact to fit in the cabinet, on the benchtop or even beneath the bench
- Easy to switch between manual aspiration and continuous aspiration mode, reducing RSI (Repetitive Strain Injury) and improving efficiency
- Collection bottle outlet with hydrophobic filter prevents aerosol and liquid contamination
- Brushless motor offers low noise and long life
- Different adapters are available to fit a multitude of laboratory supplies
- The parts in contact with liquids can be autoclaved
- Adjustable vacuum level with indicator light is designed for various applications

Specifications

Vacuum range	0-500mbar
Max. Flow	15L/min(air)
Max. aspiration speed	17mL/s(Liquid)
Bottle	2L standard, 1L optional with adaptor
Motor type	Brushless Motor
Input voltage	100-220VAC, 50/60Hz
Dimension [W×D×H]	180×240×340 mm
Weight	2.8kg

Wide range of applications

EcoVac is suitable for any application where the single liquid suction volume is less than 2L. The applicability includes use of various common consumables, which can be widely used in the collection and removal of liquids in experiments of microorganisms, molecules, proteins, cells, etc., and other applications such as RNA/DNA extraction, Western blots and ELISA.

- Aspiration of supernatants after centrifugation
- Aspiration of eluent
- Removal of supernatants during nucleic acid extraction
- Removal of culture media
- Removal of wash solutions from immuno-assay well-plate
- Removal of buffers of Western blot strips
- Removal of excess liquid from slides and Petri dishes



A	8-channel tip detrusion adapter 200µL tip
B	8 channel needle Ø1.5mm
C	Single needle Ø2.5mm, 40mm
D	Single needle Ø2.5mm, 120mm
E	Single needle Ø1.5mm, 40mm
F	Single needle Ø1.5mm, 120mm
G	tip detrusion adapter 200µL tip
H	tip detrusion adapter 1mL tip





WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.