

dFlow

Electronic Bottle-Top Dispenser

Error-free, easy to use, motorized solution

Features

- Motor controlled digital, fatigue free operation
- High quality stepper motor provides smooth and accurate dispensing
- Adjustable aspiration and dispensing speed
- Reagent recovery feature minimizes waste
- TFT display module for simple volume selection and control
- Two operation modes: continuous dispenser or stepper

Applications

Ideal for safe, accurate and precise dispensing of bases, saline solutions, acids and some organic solvents.



Specifications

Volume Range	0.1-99.9mL, Max piston lift is 10mL, resolution is 100μL
Volume Accuracy	Dispenser: R = 0.3%; CV = 0.1% Stepper: R = 0.6%; CV = 0.9%
Speed	16 Levels
Operating Temperature Range	10°C-30°C
Quality Control	DIN EN ISO 8655
Control Type	External control

* Notice: R: Relative error; CV: coefficient of variation.



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.