

## LARGE MED 600

# Glass Door: DLS700PG

## Overview

Our intuitive range refrigerators feature built-in wireless monitoring software, enabling you to access the refrigerator's performance remotely.

Plus, our bespoke touchscreen controller, designed specifically for the end user with simple access to key information.



## Key Features



### Advanced Controller

Easy to use touch screen controller, with no awkward buttons to press



### Connected

Wireless temperature monitoring built-in



### Dual Temperature Probes

View your daily minimum and maximum temperatures in one touch



### Battery Back-Up

A/V alarms should your temperature stray or the door be left open



### Antimicrobial Protection

Biocote® handle helping protect from microbes such as E. coli, Campylobacter, Salmonella and MRSA



### Self-Closing Doors

Fitted with self-closing hinges to help avoid any temperature loss

# DLS700PG - Product Specification

Counter Top	
Model	DLS700PG
Gross Capacity (Litres)	700
Net Capacity (Litres)	482
Unit External Width (mm)	720
Unit External Depth (mm)	800 (excl handle)
Unit External Height (mm)	2040
Packed Width (mm)	810
Packed Depth (mm)	910
Packed Height (mm)	2210
Packed Weight (kg)	165
Internal Dimensions (mm) (WxDxH)	600x665x1530
Temperature Range	+2C to +8C
External Finish	Pre-coated steel
Internal Finish	Stainless Steel
Type of Plastic	N/A
Door Type	Right Hand Hinged
Door Style	Glass / Self Closing
Open Door Depth	1465mm
Replaceable Door Seal	Yes
Open Door Sensor	Yes
Lock	Yes / Mechanical
Adjustable Feet	Castors x4
Porthole	Yes
Porthole Size	32mm
Temperature Display On Panel	LED / Touchscreen
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number Of Shelves	5
Number Of Shelf Positions	20
Shelf Size	530x650mm
Shelf Material	PVC coated wire
Number Of Baskets	0
Interior Light	Yes
Light Type	LED
Light Activation	Door Switch / Controller
Fan	Yes
Spark Free	No
Defrost Setting	Auto
Controller Type	Digital / Wireless
Battery Back Up	Yes
Controller Connectivity	Wireless / SD Download
Number Of Probes	2
Probe Type	Air / Load
Ambient Temperature Range	10 - 32C
Refrigerant Type	R290
Plug Type	UK
Voltage Supply	220-240V
Frequency (Hz)	50Hz
Insulation Thickness	58mm
Anti Microbial Handle	Yes / BioCote



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.