

Compact Shaker KS 15 A control



Description

The programmable Orbital Shaker KS 15 A control with digital display for reproducible shaking tasks. The loading capacity is 15 kg on a shaking platform of 400 x 300 mm.

Basic Equipment

Basic device without shaking plate, **without rack system**

With digital display and programmable control.

Loading Capacity

Erlenmeyer flasks 100 ml	20 pieces
Erlenmeyer flasks 250 ml	12 pieces
Erlenmeyer flasks 500 ml	6 pieces
Erlenmeyer flasks 1000 ml	4 pieces
Separating funnels 250 ml	1 pieces

You will find further loading possibilities [here](#)

Option:[Control interface](#)[USB interface](#)

Details

Motion:	orbital
Shaking platform:	400 x 300 mm
Max. load:	15 kg
Shaking speed:	30 - 420 rpm, in steps of 5
Stroke:	17 mm
Runtime:	programmable / continuous
Order No.:	6170 000
Accessory:	Rack System Combifix KS Universal tray KS Incubator Hood TH 15

Technical specifications

Electrical supply:	230 V or 115 V, 50 / 60 H please indicate in case of order
Enclosure protection:	IP 21
Heat emission:	approx. 10 - 15 W
Ambient temperature:	5°C to 50°C
Relative humidity:	~ 85 %
Dimensions (w x d x h):	510 x 490 x 150 mm
Weight:	19 kg



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.