


Microplate Shaker TiMix 5



Description

The Microplate Shaker TiMix 5 guarantees optimal mixing of small sample volumes in microplates, deepwell-plates or other plates in microplate format. The wide choice of different rack systems allows fastening between 8 and 48 microplates.

Basic Equipment

Basic device without shaking plate, without rack system

Loading Capacity

Standard rack system 0052 101	8 microplates
Rack system with pins 0052 096	8 microplates
Standard rack system 0052 101 + Additional tray 0052 102	16 microplates
RS high clamping pins 0052 104	24 microplates
RS metal clamping pins 0052 125	48 microplates

Details

Motion:	exact orbital motion
Shaking platform:	400 x 300 mm for 8 microplates
Max. load:	5 kg
Shaking speed:	100 - 1400 rpm, steplessly adjustable
Stroke:	3 mm
Timer:	0 - 120 min / continuous
Order No.:	6166 000
Accessory:	Standard Rack System TiMix 5 Additional tray TiMix 5 Rack System with clamping pins Rack System with high clamping pins Rack System with metal clamping pins Rack System Combifix KS Universal tray KS Incubator Hood TH 15

Technical specifications

Electrical supply:	230 V or 115 V, 50 / 60 H please indicate in case of order
Enclosure protection:	IP 21
Heat emission:	approx. 10 - 15 W
Ambient temperature:	5°C to 50°C
Relative humidity:	~ 85 %
Dimensions (w x d x h):	510 x 490 x 150 mm
Weight:	19 kg



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.