



Product Code: HR150

Refrigerated Undercounter Cabinet



Features & Benefits

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate to ISO Climate class 4 up to 32°C ambient

Shelving		Base Fittings		Doors	
Nylon Coated Shelf	Option	Castors - Rear Fixed	Standard	Solid	Standard
Refrigeration		Levelling Bolts	Standard	Left Hand Hinged Door	Option
R600a - Hydrocarbon refrigerant	Standard	Electrical & Service Data		Specification	
R134a - Industry Standard	Option	230/50/1	Standard	Refrigerator +3/+5°C	Standard
Integral Refrigeration System	Standard	220/60/1 Electrical Supply	Option	Width (mm)	605
Finish		Fuse Required (A)	10	Depth (mm)	640
s/s ext & alu int	Standard	Refrigerant Charge (kg)	0.065	Height (mm)	830
		Energy		Unpacked weight (Kgs)	69
		kWh (24 hours)	0.82	Packed weight (Kgs)	78.1
		AEC	247.29	Gross Volume (Ltr)	150
		Nett Volume	73.1	Noise dBA @ 1m	68.8
		Energy Grade	A+		
		Global Warming Potential	3		
		Energy Efficiency Index	12.51		

Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for ventilation, ensure that 50mm clearance is allowed above and around the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet



Application

This appliance is intended for use in ambient temperatures up to {1}°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.