



Product Code: HR200

Refrigerated Undercounter Cabinet with Glass Door (no light)



Features & Benefits

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate in ambient up to 25°C (ISO Climate Class 3)
- Supplied with glass door.

Shelving		Base Fittings		Doors	
Nylon Coated Shelf	Option	Castors - Rear Fixed	Standard	Glass	Standard
Refrigeration		Levelling Bolts	Standard	Specification	
R134a - Industry Standard	Standard	Electrical & Service Data		Refrigerator +3/+5°C	Standard
R290 - Energy Efficient	Option	230/50/1	Standard	Width (mm)	684
Integral Refrigeration System	Standard	Fuse Required (A)	10	Depth (mm)	780
Finish		Energy		Height (mm)	824
s/s ext & alu int	Standard	AEC	768.58	Gross Volume (Ltr)	200
		Nett Volume	98.2	Noise dBA @ 1m	69.8
		Energy Grade	C		
		Energy Efficiency Index	37.66		

Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for ventilation, ensure that 50mm clearance is allowed above and around the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet

Energy Performance Data and information



Application

This appliance is intended for use in ambient temperatures up to {1}°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.