

# Frozen in Time Ltd.

Manufacturers of Freeze Drying Machines  
and Vacuum Cold traps

## F25 Freeze drier

### UK Manufactured

The F25 freeze dryer is a short cycle, high-performance unit featuring stainless steel shelves conducting heat directly to the product rather than radiating. Freeze drying with conduction does not require such high shelf temperatures and is therefore safer for the product and easier to program.

The key features of this unit are:

- Fast drying capabilities of between 16 and 24 hours for 25kg depending on product type.
- Shelf area of 2.6m<sup>2</sup> and a shelf spacing of 60mm
- Fast initial product freezing via conduction and blast freezing.
- Clear acrylic chamber door for process observation
- LCD vacuum and temperature displays.
- Refrigeration, vacuum pump, defrost and heater switches on a touch sensitive membrane keypad with LED's to show active functions.

The F-25 is also ideal for medium scale product development and small-scale production activities.



| Technical Data                    | F25                                           |
|-----------------------------------|-----------------------------------------------|
| <b>Ice condenser capacity</b>     | 40 kg                                         |
| <b>Ice condenser performance:</b> | 30 kg / 24 h                                  |
| <b>Ice condenser temperature:</b> | -60 °C                                        |
| <b>Defrost:</b>                   | Hot gas                                       |
| <b>Shelf dimensions:</b>          | 55 × 80cm                                     |
| <b>Number of shelves:</b>         | 6 +1                                          |
| <b>Shelf area:</b>                | 2.6 m <sup>2</sup>                            |
| <b>Shelf spacing:</b>             | 6cm                                           |
| <b>Shelf temperature:</b>         | -50 °C to +90 °C                              |
| <b>Cooling systems:</b>           | Air cooled                                    |
| <b>Refrigeration:</b>             | Frigapool semi-hermetic air cooled compressor |
| <b>Unit dimensions (H×W×D):</b>   | 200cm × 120cm × 200cm                         |
| <b>Refrigerant:</b>               | R449A low GWP                                 |
| <b>Vacuum :</b>                   | Pfeiffer Duoline 20M                          |

### Part No

**F-25**

**FIT/LYO/05/1**

Please inquire for a more detailed specification and price



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.