



HRTM-18/HRTM-23



Large Capacity Water
Storage Tank



Optimized Total
Operating time



High Efficiency
Vacuum Pump

Horizontal Bench-top Autoclaves

Scope of Application

For medical, healthcare, scientific research and other related industries to disinfect medical devices, laboratory appliances and materials that may come into contact with blood or body fluids. Mainly used in ophthalmology, stomatology, beauty clinics, pet clinics, community service stations and other associated scenarios.

Innovative Design

- High degree of security by extensive safety devices
- An LCD display and touch screen control are available
- A new innovative steam generator has been developed

Product Advantages



Triple Protection of Temperature and Pressure Monitoring, Electronic Lock and Mechanical Safety Devices

When the set pressure is exceeded, the safety valve opens automatically to release the pressure.



High Degree of Security by Extensive Safety Devices

Automatic over-temperature protection, over-current, over-voltage protection and leakage protection, anti-drying protection, sensor disconnection detection, door safety protection, and full protection thermal insulated door cover.



Optimized Total Operating time

A vacuum forced cooling system and under pressure blast drying system ensures rapid sterilization, greatly shortening the sterilization time, which improves the drying effect.



4- inch LCD color screen

4- inch LCD color screen makes graphics and figures clear at a glance, easy to use.



Optional-intelligent IoT Module to Enable the Mobile APP to Monitor the Running State of the Autoclave



New Technology

Adopts a new generation steam generator to increase the saturation of the saturated steam which ensures thorough sterilization.

Ergonomic Design



Programmable Mode

The program can be edited to meet different requirements.



High Efficiency Vacuum Pump

The sterilization cycle is greatly shortened, and the sterilization and drying effects are improved.



Advanced Structure Design

One-piece stretch liner with 304 stainless steel, without dead angles and is easy to clean.



New Steam Generator Technology

An efficient steam generator with high heat exchange efficiency and large gas output has been developed to meet the requirements of rapid temperature rise and sterilization which ensures thorough sterilization of the equipment.



Large Capacity Water Storage Tank

Open water storage tank, easy to clean.

High water level display, low water level alarm, when the low water level alarm is activated, the water storage capacity will also meet the requirements of primary sterilization.



Specifications



Model	HRTM-18	HRTM-23
Design Pressure (Mpa)	0.28	0.28
Design Temperature(°C)	150	150
Rated Working Pressure (Mpa)	0.22	0.22
Sterilization Temperature Range (°C)	105-138	105-138
Temperature Control Precision (°C)	±0.1	±0.1
Dynamic Pulse Exhaust Times	0-9	0-9
Sterilization Time Range (min)	0~999	0~999
Power Supply (V/Hz)	220-240~50/60	220-240~50/60
Power (W)	2800	3200
Capacity (L)	18	23
Weight (KG)	47	53
Interior Dimension (mm)	φ247*350	φ247*450
Exterior Dimension (W*D*H) (mm)	490*600*455	490*690*455
Cabinet and Door Material	SUS304	SUS304

*Haier Biomedical reserves the right to change products and specifications without prior notice.



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.