



Mini Biological Safety Cabinet HR700-IIA2

Scope of Application:

Professional air purification equipment suitable for the test environments of small spaces and single person operations, such as virus sampling warehouses, sampling stations at airports and railway stations, on-board laboratories, and other space limited organizations.

Innovative Design

- ◉ Space-saving design with large working area
- ◉ Real-time monitoring of the airflow for safety
- ◉ Ergonomic design for single person
- ◉ Energy-efficient EBM motor



Haier Biomedical
International



Haier Biomedical
International



@haiermedicalint



Haier Biomedical
International



Haier Biomedical
International

Product Parts



EBM fan

Energy saving and low noise



Air Velocity Sensor

Intelligent constant air velocity ensures the stability

Standard Electric Glass Door

Make the use procedure more comfortable



2 Valve Interfaces

Convenient for users to use water, gas, air, etc.



Optional mobile support frame



Filters

Equipped with AAF filters, the upper filter efficiency is 99.9995% @ 0.12μm (U15), the lower filter efficiency is 99.999% @ 0.3μm (H14)



LCD display

Real-time display of operating parameters and filter life, etc

UV Lamp

One-click reservation

2 Electrical Sockets

Waterproof sockets with timing technology allows user to program timed on/off function

Cabinet Construction

Integrated 304 stainless steel work tray, 304 stainless steel work area formed on three sides

Product Advantages



Safe and reliable

Adopts AAF filters, class 1 cleanliness, provides strong protection for people, environment and samples



Interlocking function

The product features an interlocking function between UV disinfection, fluorescent lamp, front window and fan



LCD display

LCD screen displays various parameters and service life of accessories in real time, and the operational condition of the equipment is clear at a glance



Alarms

Audible and visual alarm functions: hardware failure alarm, operation parameter overrun alarm, filter and UV lamp life warning



One-click operation

UV lamp one-click reservation allows users to set 0 min to 24 hours of automatic on/off time and sterilization interval, and reduces the waiting time



Uniform airflow

- EBM fan, combined with professional air distribution design, has lower noise and more uniform air flow
- AAF filter, high efficiency and uniformity, low resistance



2 standard sockets

Waterproof socket timing technology: equipped with 2 waterproof sockets to ensure the regular opening/closing



Standard

Designed according to E.U. EN12469

Specifications

Model			HR700-IIA2
Power supply (V/Hz)			220/50/60
Power (VA)			1200
Power of Blower (W)			210
Airflow Circulation			70%Downflow, 30%Exhaust
Main Filter Typical Efficiency			≥99.999%@0.3μm (H14)
Exhaust Filter Typical Efficiency			≥99.9995%@0.12μm (U15)
Exhaust filter			Single
Filter's Brand			AAF
Downflow Velocity (m/s)			0.30
Inflow Velocity (m/s)			0.45
Lighting Intensity (Lux)			≥650
Internal Dimensions (W*D*H)	mm	600*550*540	
	in	23.62*21.65*21.26	
External Dimensions (W*D*H)	mm	700*710*1200	
	in	27.26*27.95*47.24	
Supporter (mm)			700 (optional)

Product appearance and specifications are subject to change without notice



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.