

Titramax 100



The compact model

- Titramax 100 is a compact and space-saving unit that accepts load capacities of 2 kg and space for four microtiter plates
- The 1.5-mm vibration orbit performs gentle mixing with best results using small sample volumes
- Set and continuously adjust the variable speed on the analog control knob from 150 to 1,350 rpm
- An analog process timer allows for unattended operation and can be set from 1 to 120 minutes. When the set time has elapsed an acoustic alarm will sound and the operation stops

Titramax 100 - Technical Data

Overheat protection	self-resetting
Permissible ambient conditions	5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity
Weight	5.5 kg
Protection class DIN EN 60529	IP 30
Timer	1
Rotation speed range	150 - 1,350 rpm
Power input	31 W
Dimensions (w/d/h)	245 x 310 x 125 mm
Max. Load	2 kg
Operating Mode	timer or continuous
Rotation speed setting	electronic control
Orbit / Stroke	1.5 mm
Platform size	220 x 220 mm
Accessories included	space for 4 microtiter plates
Angle	-
Motion	vibrating



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.