

Multi Reax



The all-purpose model

- Unique shaker to accommodate up to 26 vessels with various diameters. Shipment includes as a standard: Attachment for 26 vessels with diameters from 10 to 16 mm
Attachment for 12 vessels with diameters from 16 to 32 mm
- The 3-mm vibration orbit allows for excellent mixing results in large and solid samples
- Set and continuously adjust the variable speeds from 150 to 2,000 rpm on the digital display
- A digital process timer allows for unattended operation and can be set from 1 to 999 minutes. When the set time has elapsed, an acoustic alarm will sound and the operation stops

Multi Reax - Technical Data

Overheat protection	self-resetting
Permissible ambient conditions	5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity
Weight	9.8 kg
Protection class DIN EN 60529	IP 30
Timer	1
Rotation speed range	150 - 2,000 rpm
Power input	50 W
Dimensions (w/d/h)	270 x 410 x 172 mm
Max. Load	1.5 kg
Operating Mode	timer or continuous
Rotation speed setting	digital
Orbit / Stroke	3 mm
Platform size	-
Accessories included	2 carousel attachments
Angle	-
Motion	vibrating



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.