



designed for scientists



EUROSTAR 20 high speed digital

/// Data Sheet

High speed laboratory stirrer designed for intensive stirring tasks for quantities up to 20 l (H₂O). It automatically adjusts the speed through microprocessor controlled technology within the speed range of 0/150 - 6000 rpm. Safety circuits installed ensures automatic cut-off in an anti-stall or overload conditions. Continuous comparison of shaft speed to desired speed is maintained and variations are adjusted automatically. This guarantees a constant speed even with changes in viscosities of the sample. The included precision shaft is 280 mm long and has a maximum immersion depth of 220 mm.

- Digital speed display



designed for scientists

- Infinitely adjustable speed
- Cone seat for precision shaft
- Overload protection
- Short-term overload operation
- Slim casing
- Quiet operation
- Error code display



designed for scientists

Technical Data

Stirring quantity max. per stirring position (H ₂ O) [l]	20
Motor rating input [W]	176
Motor rating output [W]	125
Motor principle	Brushless DC
Speed display	7 segment LED
Speed range [rpm]	0/150 - 6000
Viscosity max. [mPas]	10000
Output max. at stirring shaft [W]	125
Permissible ON time [%]	100
Torque max. at stirring shaft [Ncm]	20
Speed control	stepless
Setting accuracy speed [±rpm]	1
Deviation of speed measurement n > 300rpm [±%]	1
Deviation of speed measurement n < 300rpm [±rpm]	3
Stirring element fastening	special output shaft
Fastening on stand	extension arm
Extension arm diameter [mm]	16
Extension arm length [mm]	220
Speed control	electronic
Nominal torque [Nm]	0.2
Housing material	alu-cast coating / thermoplastic polymer
Dimensions (W x H x D) [mm]	86 x 325 x 208
Weight [kg]	5.3
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 42
Voltage [V]	230 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	176



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.