

### Analytical Balance KERN ABP-A - Features & Accessories of the Models



Automatic sliding doors, which can be opened and closed using sensors



Ioniser (included) can be activated at the touch of a button



Opening possible alternatively via button



KERN ABP-A with integrated ioniser and internal draft shield



Erlenmeyer piston holder, included as standard with ABP 200-5M and ABP 200-5AM




Internal draft shield – minimises the effect of air currents in the weighing chamber, only for 0.01 mg models of the series ABP-A



Multi-function weighing plate, Note: included with delivery for models with [d] = 0,01 mg

#### STANDARD



#### OPTION



#### FACTORY



Model	Weighing capacity [Max] g	Readability [d] mg	Verification value [e] mg	Minimal load [Min] mg	Reproducibility mg	Linearity mg	Options	
							Verification	DAkkS Calibr. Certificate
<b>KERN</b>							<b>M</b>	<b>DAKKS</b>
<b>ABP 100-5AM</b>	135	0,01	1	1	0,05	± 0,1	965-201	963-101
<b>ABP 200-5AM</b>	220	0,01	1	1	0,05	± 0,1	965-201	963-101
<b>ABP 200-4AM</b>	220	0,1	1	10	0,1	± 0,2	965-201	963-101
<b>ABP 300-4AM</b>	320	0,1	1	10	0,2	± 0,3	965-201	963-101
Multi-division balance, with increasing or decreasing load, it switches automatically to the next largest or smallest weighing range [Max] and readout [d].								
<b>ABP 100-5DAM</b>	52   120	0,01   0,1	1   1	1	0,02   0,1	± 0,05   0,2	965-201	963-101
<b>ABP 200-5DAM</b>	102   220	0,01   0,1	1   1	1	0,05   0,1	± 0,1   0,2	965-201	963-101

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

<p><b>Internal adjusting</b> Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)</p>	<p><b>Interface for second balance</b> For direct connection of a second balance</p>	<p><b>Hold function</b> (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value</p>	<p><b>Conformity Assessment</b> The time required for conformity assessment is specified in the pictogram</p>
<p><b>Adjusting program CAL</b> For quick setting up of the balance's accuracy. External adjusting weight required</p>	<p><b>Network interface</b> For connecting the scale to an Ethernet network</p>	<p><b>Protection against dust and water splashes IPxx</b> The type of protection is shown in the pictogram</p>	<p><b>DAkkS calibration possible (DKD)</b> The time required for DAkkS calibration is shown in days in the pictogram</p>
<p><b>EasyTouch</b> Suitable for the connection, data transmission and control through PC or tablet</p>	<p><b>KERN Communication Protocol (KCP)</b> It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems</p>	<p><b>Suspended weighing</b> Load support with hook on the underside of the balance</p>	<p><b>Factory calibration (ISO)</b> The time required for Factory calibration is shown in days in the pictogram</p>
<p><b>Memory</b> Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.</p>	<p><b>GLP/ISO log intern</b> The balance displays weight, date and time, independent of a printer connection</p>	<p><b>Battery operation</b> Ready for battery operation. The battery type is specified for each device</p>	<p><b>Package shipment</b> The time required for internal shipping preparations is shown in days in the pictogram</p>
<p><b>Alibi memory</b> Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.</p>	<p><b>GLP/ISO log Printer</b> With weight, date and time. Only with KERN printers.</p>	<p><b>Rechargeable battery pack</b> Rechargeable set</p>	<p><b>Pallet shipment</b> The time required for internal shipping preparations is shown in days in the pictogram</p>
<p><b>KERN Universal Port (KUP)</b> allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WIFI, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort</p>	<p><b>Piece counting</b> Reference quantities selectable. Display can be switched from piece to weight</p>	<p><b>Universal plug-in power supply</b> with universal input and optional input socket adapters for A) EU, CH, GB B) EU, CH, GB, US C) EU, CH, GB, US, AUS</p>	
<p><b>RS-232 Data interface</b> To connect the balance to a printer, PC or network</p>	<p><b>Recipe level A</b> The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out</p>	<p><b>Plug-in power supply</b> 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available</p>	
<p><b>RS-485 Data interface</b> To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible</p>	<p><b>Recipe level B</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display</p>	<p><b>Integrated power supply unit</b> Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request</p>	
<p><b>USB Data interface</b> To connect the balance to a printer, PC or other peripherals</p>	<p><b>Totalising level A</b> The weights of similar items can be added together and the total can be printed out</p>	<p><b>Weighing principle Strain gauges</b> Electrical resistor on an elastic deforming body</p>	
<p><b>Bluetooth* Data interface</b> To transfer data from the balance to a printer, PC or other peripherals</p>	<p><b>Percentage determination</b> Determining the deviation in % from the target value (100 %)</p>	<p><b>Weighing principle Tuning fork</b> A resonating body is electromagnetically excited, causing it to oscillate</p>	
<p><b>WIFI Data interface</b> To transfer data from the balance to a printer, PC or other peripherals</p>	<p><b>Weighing units</b> Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details</p>	<p><b>Weighing principle Electromagnetic force compensation</b> Coil inside a permanent magnet. For the most accurate weighings</p>	
<p><b>Control outputs</b> (optocoupler, digital I/O) To connect relays, signal lamps, valves, etc.</p>	<p><b>Weighing with tolerance range (Checkweighing)</b> Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model</p>	<p><b>Weighing principle Single cell technology</b> Advanced version of the force compensation principle with the highest level of precision</p>	
<p><b>Analogue interface</b> to connect a suitable peripheral device for analogue processing of the measurements</p>			

\* The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.