

Digital microscope sets KERN OBE-S


































Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories

| Features | Technical data |
|----------|----------------|
|----------|----------------|

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• Laboratory microscopes from the OBE range are now also available to you as a comprehensive digital solution for your live investigations. Optionally available with an mounted tablet or C-mount camera. Naturally, the appropriate C-mount adapter is included with the delivery</li> <li>• The mounted KERN ODC 241 tablet-camera has been specially developed for simple, convenient and direct investigation of the sample on the screen. Ideally suited for school pupils and students in education or for demonstration purposes in the laboratory</li> </ul> | <ul style="list-style-type: none"> <li>• The mounted C-mount camera is available in different versions and can be used anywhere</li> <li>• For detailed information on the individual components, see the relevant product description of the individual item</li> <li>• A protective dust cover, eye cups, as well as multi-lingual user instructions are included in the scope of the delivery</li> </ul> |
| <ul style="list-style-type: none"> <li>• Finite optical system</li> <li>• Quadplex nosepiece</li> <li>• Siedentopf 30° inclined/360° rotatable</li> <li>• Diopter adjustment: One-sided</li> <li>• Eyepiece: HWF 10×/ø 18 mm</li> <li>• Objective quality: Achromatic</li> <li>• Objectives OBE 124: 4×/10×/40×</li> <li>• Objectives OBE 134: 4×/10×/40×/100×</li> <li>• Illumination: 3 W LED (transmitted)</li> <li>• Overall dimensions W×D×H 320×180×365 mm</li> <li>• Net weight approx. 5,5 kg</li> </ul>   |   |

| Model              | Standard configuration (camera) |                   |                                       |             |                                      |
|--------------------|---------------------------------|-------------------|---------------------------------------|-------------|--------------------------------------|
| KERN               | Included camera                 | Resolution camera | Interface                             | Sensor      | Details microscope, camera           |
| <b>OBE 124C825</b> | ODC 825                         | 5 MP              | USB 2.0 (6,8 – 55 FPS)                | CMOS 1/2,5" | _____                                |
| <b>OBE 134C825</b> |                                 |                   |                                       |             | _____                                |
| <b>OBE 124C832</b> | ODC 832                         | 5 MP              | USB 3.0 (14,2 – 101,2 FPS)            | CMOS 1/2,5" | KERN Optics catalogue<br>Page 14, 86 |
| <b>OBE 134C832</b> |                                 |                   |                                       |             | _____                                |
| <b>OBE 124T241</b> | ODC 241                         | 5 MP              | WiFi, USB 2.0, HDMI, SD (15 – 30 FPS) | CMOS 1/2,5" | KERN Optics catalogue<br>Page 14, 90 |
| <b>OBE 134T241</b> |                                 |                   |                                       |             | _____                                |

- 
**360° rotatable microscope head**
- 
**Monocular Microscope**  
 For the inspection with one eye
- 
**Binocular Microscope**  
 For the inspection with both eyes
- 
**Trinocular Microscope**  
 For the inspection with both eyes and the additional option for the connection of a camera
- 
**Abbe Condenser**  
 With high numerical aperture for the concentration and the focusing of light
- 
**Halogen illumination**  
 For pictures bright and rich in contrast
- 
**LED illumination**  
 Cold, energy-saving and especially long-life illumination
- 
**Incident illumination**  
 For non-transparent objects
- 
**Transmitting illumination**  
 For transparent objects
- 
**Fluorescence illumination**  
 For stereomicroscopes
- 
**Fluorescence illumination for compound microscopes**  
 With 100 W mercury lamp and filter
- 
**Fluorescence illumination for compound microscopes**  
 With 3 W LED illumination and filter
- 
**Phase contrast unit**  
 For a higher contrast
- 
**Darkfield condenser/unit**  
 For a higher contrast due to indirect illumination
- 
**Polarising unit**  
 To polarise the light
- 
**Infinity system**  
 Infinity corrected optical system
- 
**Zoom magnification**  
 For stereomicroscopes
- 
**Auto-focus**  
 For automatic control of the focus level
- 
**Parallel optical system**  
 For stereomicroscopes, enables fatigue-proof working
- 
**Integrated scale**  
 In the eyepiece
- 
**SD card**  
 For data storage
- 
**USB 2.0 digital camera**  
 For direct transmitting of the picture to a PC
- 
**USB 3.0 digital camera**  
 For direct transmitting of the picture to a PC
- 
**WiFi data interface:**  
 For transmitting of the picture to a mobile display device
- 
**HDMI digital camera**  
 For direct transmitting of the picture to a display device
- 
**PC software**  
 To transfer the measurements from the device to a PC.
- 
**Automatic temperature compensation**  
 For measurements between 10 °C and 30 °C
- 
**Protection against dust and water splashes IPxx:**  
 The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013
- 
**Battery operation**  
 Ready for battery operation. The battery type is specified for each device.
- 
**Battery operation rechargeable**  
 Prepared for a rechargeable battery operation
- 
**Plug-in power supply**  
 230V/50Hz in standard version for EU. On request GB, AUS or USA version.
- 
**Integrated power supply unit**  
 Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
- 
**Package shipment**  
 The time required to manufacture the product internally is shown in days in the pictogram.

## ABBREVIATIONS

- C-Mount** Adapter for the connection of a camera to a trinocular microscope
- FPS** Frames per second
- H(S)WF** High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)
- LWD** Long Working Distance
- N.A.** Numerical Aperture
- SLR camera** Single-Lens Reflex camera
- SWF** Super Wide Field (Field number at least  $\varnothing$  23 mm for 10 $\times$  eyepiece)
- W.D.** Working Distance
- WF** Wide Field (Field number up to  $\varnothing$  22 mm for 10 $\times$  eyepiece)



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.