


Inverted microscope KERN OCM-1



OCM 161



OCM 165-168



N.A. 0,3 Abbe Condenser with phase contrast slide



Coaxial control knobs for x/y can be fitted either left or right

LAB LINE

The inverted biological laboratory microscope – also with fluorescence

Features

- The OCM range stands out through its design which is ergonomic, robust and extremely stable. This design, with its large working distance, is particularly suitable for the monitoring and analysis of cell cultures, for example
- A strong and continuously adjustable 30W halogen illumination unit ensures the optimum illumination in the bright field of your samples. In addition, either an Osram 100 W-HBO- (OCM 165/166) or a 5 W-LED Epi fluorescence incident illumination unit (OCM 167/168) are available to you as a fluorescence microscope for perfect illumination and stimulation of your fluorescence samples
- A special Abbe N.A. 0.3 condenser with aperture diaphragm and large working distance of 72 mm guarantees the very best working practise in the bright field and with fluorescence applications

- As standard, the OCM range is fitted with a trinocular eyepiece tube
- The mechanical stage including specimen holder (\varnothing 110 mm) means that you can work quickly and effectively. Further brackets for petri dishes are included with delivery or available as accessories
- Further options such as, for example, a selection of eyepieces, objectives, specimen holders and other phase contrast units can be integrated as accessories
- A dust cover as well as user instructions are included with the delivery
- Please find detailed information in the following model outfit list

Scope of application

- Research and breeding of cell cultures and tissue cultures

Applications/Samples

- Particularly for viewing samples in culture vessels (flasks, petri dishes, microtitre plates), translucent, thin, low-contrast, challenging samples (e.g. living mammal cells, tissue, microorganisms if necessary, immunofluorescence, FISH, DAPI staining etc.)

Technical data

- Infinity optical system
- Quintuple nosepiece
- Siedentopf 45° inclined
- Diopter adjustment: Both-sided

OCM 161

- Overall dimensions WxDxH 304x599x530 mm
- Net weight approx. 13,5 kg

OCM 165-168

- Overall dimensions WxDxH 304x782x530 mm
- Net weight approx. 21 kg

STANDARD



Model

Standard configuration































KERN	Tube	Eyepiece	Objective quality	Objectives	Illumination
OCM 161	Trinocular	HWF 10x/ \varnothing 22 mm	Infinity Plan		30 W Halogen (transmitted)
OCM 165	Trinocular	HWF 10x/ \varnothing 22 mm	Infinity Plan		30 W Halogen + 100 W Epi Fluorescence (B/G)
OCM 166	Trinocular	HWF 10x/ \varnothing 22 mm	Infinity Plan	LWD10x/LWD20x/ LWD40x/LWD20xPH	30 W Halogen + 100 W Epi Fluorescence (UV/V/B/G)
OCM 167	Trinocular	HWF 10x/ \varnothing 22 mm	Infinity Plan		5W-LED + 5W Epi Fluorescence (B/G)
OCM 168	Trinocular	HWF 10x/ \varnothing 22 mm	Infinity Plan		5W-LED + 5W Epi Fluorescence (UV/V/B/G)

Inverted microscope KERN OCM-1

Model outfit		Model KERN					Order number
		OCM 161	OCM 165	OCM 166	OCM 167	OCM 168	
Eyepieces (30 mm)	HWF 10×/∅ 22 mm (adjustable)	✓✓	✓✓	✓✓	✓✓	✓✓	OBB-A1491
	HWF 10×/∅ 22 mm (reticule 0,1 mm) (adjustable)	○	○	○	○	○	OBB-A1523
Infinity Plan achromatic Fluor objectives for long working distance	4×/0,11 W.D. 12,1 mm	○	○	○	○	○	OBB-A1600
	10×/0,25 W.D. 10,3 mm	✓	✓	✓	✓	✓	OBB-A1601
	20×/0,40 W.D. 5,8 mm	✓	✓	✓	✓	✓	OBB-A1602
	40×/0,60 W.D. 5,1 mm	✓	✓	✓	✓	✓	OBB-A1603
Trinocular tube	<ul style="list-style-type: none"> • 45° inclined • Interpupillary distance 48–76 mm • Light distribution 100:0 • Diopter adjustment: Both-sided 	✓	✓	✓	✓	✓	
Mechanical stage	<ul style="list-style-type: none"> • Stage size W×D 210×241 mm • Travel 128×80 mm • Coaxial coarse and fine focusing knobs • The x/y control knobs can be fitted either left or right • Suitable for attaching a 96-hole microtitre plate 	✓	✓	✓	✓	✓	
	Drop specimen holder (∅ 110)	✓	✓	✓	✓	✓	OBB-A1503
	Specimen holder for 35 mm culture dish	○	○	○	○	○	OBB-A1507
	Specimen holder for 54 mm culture dish	✓	✓	✓	✓	✓	OBB-A1506
	Specimen holder for 65 mm culture dish	○	○	○	○	○	OBB-A1505
Condenser	Abbe N.A. 0,3 (aperture diaphragm), LWD 72 mm	✓	✓	✓	✓	✓	
Illumination	30 W Halogen spare bulb (transmitted)	✓	✓	✓			OBB-A1372
	5 W LED spare bulb (transmitted)				✓	✓	OBB-A1589
Phase contrast units	Phase contrast slide 4x	○	○	○	○	○	OBB-A1608
	Phase contrast slide 10x	✓	✓	✓	✓	✓	OBB-A1609
	Phase contrast slide 20x/40x	✓	✓	✓	✓	✓	OBB-A1610
	Infinity PH-Plan Fluor objective 4×	○	○	○	○	○	OBB-A1604
	Infinity PH-Plan Fluor objective 10x	○	○	○	○	○	OBB-A1605
	Infinity PH-Plan Fluor objective 20x	✓	✓	✓	✓	✓	OBB-A1606
	Infinity PH-Plan Fluor objective 40x	○	○	○	○	○	OBB-A1607
	Centering eyepiece	○	○	○	○	○	OBB-A1544
Fluorescence unit	100 W HBO Epi Fluorescence unit, two-hole slide (B/G)		✓				
	100 W HBO Epi Fluorescence unit, four-hole slide (UV/V/B/G)			✓			
	5 W HBO Epi Fluorescence unit, two-hole slide (B/G)				✓		
	5 W HBO Epi Fluorescence unit, four-hole slide (UV/V/B/G)					✓	
Colour filters for transmitted illumination	Blue	✓	✓	✓	✓	✓	OBB-A1510
	Green	✓	✓	✓	✓	✓	OBB-A1511
	Yellow	○	○	○	○	○	OBB-A1512
	Grey	○	○	○	○	○	OBB-A1513
C-Mount	0,5×	○	○	○	○	○	OBB-A1515
	1×	○	○	○	○	○	OBB-A1514

✓ = Included with delivery

○ = Option

- 
360° rotatable microscope head
- 
Monocular Microscope
 For the inspection with one eye
- 
Binocular Microscope
 For the inspection with both eyes
- 
Trinocular Microscope
 For the inspection with both eyes and the additional option for the connection of a camera
- 
Abbe Condenser
 With high numerical aperture for the concentration and the focusing of light
- 
Halogen illumination
 For pictures bright and rich in contrast
- 
LED illumination
 Cold, energy-saving and especially long-life illumination
- 
Incident illumination
 For non-transparent objects
- 
Transmitting illumination
 For transparent objects
- 
Fluorescence illumination
 For stereomicroscopes
- 
Fluorescence illumination for compound microscopes
 With 100 W mercury lamp and filter
- 
Fluorescence illumination for compound microscopes
 With 3 W LED illumination and filter
- 
Phase contrast unit
 For a higher contrast
- 
Darkfield condenser/unit
 For a higher contrast due to indirect illumination
- 
Polarising unit
 To polarise the light
- 
Infinity system
 Infinity corrected optical system
- 
Zoom magnification
 For stereomicroscopes
- 
Auto-focus
 For automatic control of the focus level
- 
Parallel optical system
 For stereomicroscopes, enables fatigue-proof working
- 
Integrated scale
 In the eyepiece
- 
SD card
 For data storage
- 
USB 2.0 digital camera
 For direct transmitting of the picture to a PC
- 
USB 3.0 digital camera
 For direct transmitting of the picture to a PC
- 
WiFi data interface:
 For transmitting of the picture to a mobile display device
- 
HDMI digital camera
 For direct transmitting of the picture to a display device
- 
PC software
 To transfer the measurements from the device to a PC.
- 
Automatic temperature compensation
 For measurements between 10 °C and 30 °C
- 
Protection against dust and water splashes IPxx:
 The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013
- 
Battery operation
 Ready for battery operation. The battery type is specified for each device.
- 
Battery operation rechargeable
 Prepared for a rechargeable battery operation
- 
Plug-in power supply
 230V/50Hz in standard version for EU. On request GB, AUS or USA version.
- 
Integrated power supply unit
 Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
- 
Package shipment
 The time required to manufacture the product internally is shown in days in the pictogram.

ABBREVIATIONS

- C-Mount** Adapter for the connection of a camera to a trinocular microscope
- FPS** Frames per second
- H(S)WF** High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)
- LWD** Long Working Distance
- N.A.** Numerical Aperture
- SLR camera** Single-Lens Reflex camera
- SWF** Super Wide Field (Field number at least \varnothing 23 mm for 10 \times eyepiece)
- W.D.** Working Distance
- WF** Wide Field (Field number up to \varnothing 22 mm for 10 \times eyepiece)



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.