

Control Plus

Upright Control Plus Solid Door Refrigerator 273L

GDPA code **PPSR273UK**

SKU code **444410651**



Key features

- ✓ 2°C to 8°C temperature range
- ✓ Air and core temperature display
- ✓ Represents your vaccine vial
- ✓ External digital controller and temperature display
- ✓ Fitted lock and 2 keys
- ✓ Audible and visual temperature alarms
- ✓ 5 year warranty as standard



New controller

New updated Controller system for improved user experience. Read, Record, Reset simply with the touch of one button, with no stress of accidentally resetting on the clear digital display.

Dual probe

Greater temperature accuracy given from two temperature probe readings. One probe measuring air temperature and one measuring load (or product) temperature.

Porthole

Factory fitted 16mm porthole enables quick and easy access for any secondary temperature monitoring probes.

Flexible internal storage

Multiple shelf locations along with a wire basket provides a flexible storage solution.

Anti-microbial handle

Powder coated to help prevent cross contamination by inhibiting the growth of microbes.

Specification: Upright Control Plus Solid Door Refrigerator 273L

Gross Capacity (litres)	273L
Net Capacity (litres)	269L
Unit External Width (mm)	595mm
Unit External Depth (mm)	625mm
Unit External Height (mm)	1565mm
Product Weight (kg)	60kg
Packed Width (mm)	650mm
Packed Depth (mm)	727mm
Packed Height (mm)	1585mm
Packed Weight (kg)	65kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	480mm W x 1382mm H x 445mm
Temperature Range	+2°C to +8°C (set point tolerance + or - 2)
Colour	White/Green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Flat
Door Open Depth (mm)	1185mm
Replacement Door Seal	No
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 adjustable front feet, 2 rear rollers
Porthole	Yes
Porthole Size	16 mm
Porthole Location	Rear Bottom
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves	5
Number of Shelf Positions	12
Shelf Size (mm) (WxDxH)	4 x 385mm W x 6mm H x 500mm D 1 x 340mm x 6mm H x 497mm D
Shelf Material	Wire
Number of Baskets	1
Basket Material	Wire
Basket Size (mm) (WxDxH)	
Interior Light	Yes
Light Type	Halogen
Light Activation	Controller
Fan	Yes
Spark Free	No
Defrost setting	Auto
Controller Type	Digital, External
Number of Probes	2
Probe Type	Air & Load (Glycol Solution)
Ambient Temperature Range	10 to 32
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
UK 3 Pin Plug	Yes
Other Plug Types Available	Yes
Voltage Supply	220-240
Insulation Thickness (mm)	60mm
Insulation Type	High Density Polyurethane Foam
Blowing Agent	Cyclopentane
Anti Microbial Handle	Yes
Wall Brackets	No
Optional Drawer System	No
Optional Digital Lock	PPSR273UK-DWP - 444410654
Other Door Option	Glass PPGR273UK - 444410651



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.