



RLPR0517-ATEX Under Counter Sparkfree ATEX Refrigerator

Part Number	RLPR0517-ATEX
Capacity (Litres)	150
Style	Under Bench
Exterior Dimensions (HxWxD)	835 x 600 x 600mm
Interior Dimensions (HxWxD)	690 x 480 x 410mm
Weight	45kg
Energy Consumption	1.1kWh/24hr
Operating Temperature	+0°C to +10°C
Factory Set Point	+5°C
Interior Construction	Painted Aluminium
Exterior Construction	Powder Coated Steel
Door Style	Self Closing
Door Hinging	Right (can be reversed please ask at time of order)
Door Lock	✓
Door Earth Connection	✓
Condensate Collection	✓
Shelves	3
Shelf dimension (WxD)	2 x 475 x 385mm 1 x 475 x 245mm
Spare shelves available	✓
Feet	4
Temperature Display	✓
High Temperature Alarm	✓
Low Temperature Alarm	✓
Door Open Alarm	✓
Off Cycle Auto Defrost	✓
Low GWP Refrigerant	✓
2 Year Warranty (UK only)	✓

The Labcold ATEX refrigerator range has been designed with an interior which is licensed as a Zone 2 hazardous area under 2014/34/EU (ATEX Directive) in order to store products which are classed in explosion group IIB+H2 and temperature class T6 under 2014/34/EU (ATEX Directive).

Warning: Do not store open containers of volatile substances in this fridge.



CLAIM
YOUR
FREE
YEAR
WARRANTY

All Labcold sparkfree ATEX refrigerators are fitted with a cylinder lock with two keys and a controller with a digital temperature display. The controller also features a high/low audio and visual temperature alarm in addition to a door open alarm.



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.