



- Extensive Range
- 90+ Years of History
- Extended Aftercare Support
- UKAS Laboratory

Intellicold® Pharmacy Fridges

Undercounter RLDF0524

A next generation pharmacy refrigerator featuring the latest IntelliCold® 24-Range technology, designed for the safe storage of cold chain medicines in line with Public Health England guidance.

An enhanced IntelliCold® touch screen controller delivers accurate timekeeping, intelligent event logging and Bluetooth connectivity for fast access to temperature data via the Labcold Connect Android App. The flat, easy-clean controller locks automatically to prevent accidental changes.

Inside, three independent temperature probes provide advanced protection, including a low-temperature safeguard that prevents freezing. A pre-fitted simulated load has been carefully selected to represent the thermal behaviour of commonly stored pharmacy products. This ensures temperature readings reflect true product conditions, providing meaningful alarms when medicines are genuinely at risk; rather than masking excursions with oversized or unrepresentative loads.

Each unit is supplied with a FREE UK 5-year warranty for complete peace of mind. A UKAS temperature calibration certificate (Lab No. 8898) is available at an extra cost if required.

Specifications

Product Code	RLDF0524
Gross Capacity	150 Liters
Style	Under Counter
UK Warranty	5 Years
External Dimensions (mm) HxWxD	835 x 600 x 600
Internal Dimensions (mm) HxWxD	690 x 480 x 410
Temperature Range	2°C to 8°C
Fridge Set Point	5°C

Specifications (cont.)

Internal Material	Powder Coated Steel
External Material	Powder Coated Steel
Shelves	3
Net Weight	54 Kg
Door Style	Solid
Lock Type	Key Lock
Brackets for wall mounting	No
Digital Temperature Display	Yes
Digital Temperature Control	Yes
High/Low Temperature Alarm	Yes
Min/Max Temperature Recording	Yes
Integral Temp Data Logging	Yes
Automatic Temperature & Fridge Operation Data	Yes
Number of Temperature Probes	3
Internal Light	Yes
Self Closing Door	Yes
Door Open Alarm	Yes
Mains Failure Alarm	Yes
Alarm Battery Backup	Yes
Auto Defrost	Yes
Fan Assisted Cooling	Yes
Remote Alarm Contacts	Yes
Access Porthole	Yes
Access Porthole Size	12mm
Power Consumption Kwh/24hrs	1.4
Ambient Operating Temperature	16°C to 32°C

Features

- FREE UK 5-year warranty
- 24/7 automatic temperature logging which is accessible via Bluetooth (Labcold Connect Android App)
- Fan assisted cooling
- T3 Sensor & Low-temperature cut
- Controller and alarm battery back up
- Power failure alarm
- Minimum/maximum temperature recording and display
- Fan assisted cooling
- Environmentally friendly refrigerant
- Internal light
- Compliant with all leading professional guidelines
- Fitted with the IntelliCold® touch screen controller
- Event based logging
- Door lock with two keys
- Realistic pre-fitted simulated load
- Door open alarm
- High/Low temperature alarm
- Auto defrost
- Access port for additional monitoring equipment
- Self-closing door
- Remote alarm contacts

Models

	Model	Gross Capacity	Door Style	Lock Type
	Undercounter RLDF0519 Diglock	150 litres	Solid	Digital Lock
	Undercounter RLDG0519	150 litres	Solid	Key Lock
	Undercounter RLDG0519 Diglock	150 litres	Glass	Digital Lock
	Undercounter RLDF0524	150 Liters	Solid	Key Lock

Accessories



Labcold Stacking Kit



Divided Drawer for
RLDF/G0519 and
RLBM0519



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.