

Chest freezer LT C300



- Low cost of ownership
- Limited maintenance
- On-site service

- Easily installable & movable
- Efficient cyclopentane insulation
- ISO 9001, 14001 & 45001 Certified

Specifications	
Technical	
Gross volume	296 litres
Net Volume	284 litres
Temp. range	-25°C to -45°C
Temp. probes	1/PTC
Compressor	Embraco
Baskets (incl./optional)	1/12
Refrigerant	R 290
Noise level	55 dB
Power consumption 24/h	3,7 kWh
Power consumption	1.365 kWh / year
Voltage	230V
Frequency	50 Hz
Features	
Audible & visual alarm	YES
Castors	4
Integrated lock	YES
Inner lids	NO
Defrost	Manual
Battery Backup	NO
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø12 mm
Connection for remote alarm	Optional
Material	
Inner	Precoated white steel
Outer	Galvanized pre-coated steel
Outer dimensions	
Height (with castors)	885 mm
Width	1.260 mm
Depth (Incl. condenser)	630 mm
Depth (Incl. condenser)	680 mm
Net weight	71 kg
Inner dimensions	
Height	635/385 mm
Width	1100/890 mm
Depth	440 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %

LT C300	
	
Product no.	N111003

Storage capacity				
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	6	3	18	N311200
	11	18	198	N311220
			= 216	
75 mm	4	3	12	N311300
	8	18	144	N311320
			= 156	
100 mm	3	3	9	N311400
	5	18	90	N311420
			= 99	



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.