



Technical Features

Net Storage Volume	662 lt (23,38 cu ft)
Temperature Range	+20°C/+50°C
Relative Humidity Range	30%/80%
T Stability/Uniformity	± 1,5°C
RH Stability/Uniformity	± 5%
Ambient Operating Temperature	+10°C/+38°C, 50% RH (N-ST Climate Class)
Noise Level	< 49 dBA

Power Supply	230V ±10% / 50Hz
Standard Electrical Plug	Schuko
Power Absorption (max)	8A

External Dimensions	W 1040 x D 905 x H 2010 mm W 40,94 x D 35,63 x H 79,13 inch.
Internal Dimensions	W 920 x D 610 x H 1180 mm W 36,22 x D 24,02 x H 46,46 inch.
Weight	250 kg

Packing Dimensions	Carton Box + Pallet: W 1150 x D 1000 x H 2200 mm, 260 kg Wooden Crate: W 1200 x D 1300 x H 2300 mm, 330 kg
---------------------------	---

External Surface	Galvanized steel with anti-bacterial coating
Internal Surface	AISI 304 18/10 stainless steel
External/Internal Edges	Rounded to facilitate easy cleaning
Insulation Thickness	60 mm on sides / 60 mm rear (Mineral fibers)
Door Type	Solid, with self-closing system (with opening angle ≤90°), recessed groove handle
Door Sealing	Magnetic silicone gasket placed all over the door's frame

Standard Configuration	Tempered glass inner door n°3 AISI 304 stainless steel grid shelves, height adjustable (W 905 x D 600 mm) with max load 35 kg each n°4 swivel castors (front castors equipped with brakes) Porthole (Ø 25 mm) for independent probes connected to external monitoring system/BMS Backup battery with self-charging circuit (48 hours autonomy in case of power failure) Volt-free contact for connection to an external alarm monitoring system RFI filter
-------------------------------	--

Cooling/Heating/Relative Humidity Systems

Cooling	Forced-air cooling, with automatic shut-off of the evaporator fan during door opening
Heating	Obtained with specific heating elements with low thermal density
Heat Exchangers	Placed in a separate area from the internal chamber, for an high uniform thermostating
Thermostatic Flow	Driven by a high efficiency helical fan
Compressor	Fully sealed hermetic compressor with thermal protector
Refrigerant (CFC/HCFC free)	R134a
Humidity	Psychrometric principle, T difference constant between internal air and counter-base water tank.

HPL Control System

Controller	Microprocessor Controller
Display	7" LED touch screen display with 0.1°C resolution
Temperature Probes	n°2 Pt100 Class A
Access Control	3-levels password security system (User/Service/Admin)
Data Export	USB port, SD card slot, RJ45 port (ModBus TCP protocol) for LAN connection to PC/BMS The main screen displays the T set point, real time T graph, high/low T limits, battery level, date/time Data logger function with automatic recording of temperature data (at 30-seconds intervals) and events
Features	Internal memory (built-in 4GB SD card) capable of recording data for a minimum period of 10 years Data history menu for consultation and selection of temperature data records, events and alarms of the device In-built power stabilizer with linear voltage regulation (±20 Volts) - Power failure - Door open (the alarm interval can be freely set by the user) - High/Low temperature (alarm limits can be set freely by the user) - Temperature probes failure - Back-up battery failure / low charge
Main Alarms List (Audio/visual notification)	





TECNILABO

Thermal Cycles

- Program/segment/remaining time on display
- Program execution repetitions: from 0 to 9999
- 1 program with 32 segments
- 2 programs with 16 segments each
- 8 programs with 4 segments each

Accessories Available On Request

- Additional adjustable AISI 304 stainless steel grid shelf
- Additional internal/external porthole (Ø 25 mm)
- Weekly cycle chart disk recorder (including n°52 spare paper disks + n°1 pen)
- Voltage stabilizer
- GSM module with SIM card bridge
- Wi-Fi kit (TCP/IP Modbus) for connection to BMS/SCADA and remote monitoring
- Electrical outlet different from standard Shucko
- Extended temperature probes for pharma industry
- Internal power socket
- Packing in wooden cage



Adjustable wire shelf



Swivel castor with brake



Int/Ext. Porthole



Remote alarm contacts



Door gasket



HPL controller



Door switch



Internal power socket (optional)



Voltage stabilizer (optional)



7-days Chart recorder (optional)



Wooden crate (optional)



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.